


UL LISTED AND CSA APPROVED WIRE CONNECTORS



- Five color-coded models cover a full range of wire sizes from 22 through 8 AWG
- Fixed, square-wire spring creates its own threads – maintains a secure positive grip that will not relax over time
- No pre-twisting required – positive grip design provides fast, easy installation
- Deep, wide skirt helps protect against flash-over and turned-back strands for maximum dielectric protection
- Reusable for easy circuit changes and additions
- Tough, UL94V-2 flame-retardant shell rated at 105°C (221°F)
- UL 486C Listed and CSA 22.2 #188 Certified; comply with Federal Specification W-S-610E
- Classified in accordance with IEC Publications 998-2 and 998-2-4



Model	Color	Wire Combination Range	Wire Combination Range (mm)	Quantity	Cat. No.
71B®	Gray	300V No. 22 to 16 AWG Min. 2 No. 22 Max. 2 No. 16	300V .64mm DIA to 1.29mm DIA Min. .65mm ² Max. 2.62mm ²	Box of 100 Carton of 1,000 Keg of 25,000 (loose pack) Card of 14	30-071 30-171 30-271 30-771
72B®	Blue	300V No. 22 to 14 AWG Min. 2 No. 22 Max. 3 No. 16	300V .64mm DIA to 1.63mm DIA Min. .65mm ² Max. 3.93mm ²	Box of 100 Carton of 1,000 Keg of 10,000 (loose pack) Card of 12	30-071 30-172 30-272 30-772
73B®	Orange	600V* No. 22 to 14 AWG Min. 1 No. 18 & 1 No. 20 Max. 4 No. 16 & 1 No. 20	600V* .64mm DIA to 1.63mm DIA Min. 1.34mm ² Max. 5.76mm ²	Box of 100 Jar of 300 Carton of 1,000 Keg of 10,000 (20 bags, 500 ea.) Keg of 10,000 (loose pack) Card of 10	30-073 30-073J 30-173 30-273 30-673 30-773
74B®	Yellow	600V* No. 18 to 12 AWG Min. 2 No. 18 Max. 4 No. 14 & 1 No. 18	600V* 1.02mm DIA to 2.05mm DIA Min. 1.64mm ² Max. 9.14mm ²	Box of 100 Jar of 175 Carton of 1,000 Keg of 10,000 (20 bags, 500 ea.) Keg of 10,000 (loose pack) Card of 8	30-074 30-074J 30-174 30-274 30-674 30-774
76B®	Red	600V* No. 18 to 10 AWG Min. 2 No. 14 Max. 2 No. 10 & 2 No. 12	600V* 1.02mm DIA to 2.59mm DIA Min. 4.16mm ² Max. 17.14mm ²	Box of 100 Carton of 1,000 Keg of 5,000 (20 bags, 250 ea.) Card of 6	30-076 30-176 30-276 30-776

*1,000V maximum in fixtures and signs

