

SELF PIERCING DRIPPERS



SELF PIERCING DRIPPERS w/ CHECK VALVE

Part #	Description	bag ct
SPCV05-25	0.5 gph barb inlet x .160 barb outlet	25
SPCV05-100	0.5 gph barb inlet x .160 barb outlet	100
SPCV05-250	0.5 gph barb inlet x .160 barb outlet	250
SPCV05-1000	0.5 gph barb inlet x .160 barb outlet	1000
SPCV10-25	1.0gph barb inlet x .160barb outlet	25
SPCV10-100	1.0gph barb inlet x .160barb outlet	100
SPCV10-250	1.0gph barb inlet x .160barb outlet	250
SPCV10-1000	1.0gph barb inlet x .160barb outlet	1000
SPCV20-25	2.0gph barb outlet x .160 barb outlet	25
SPCV20-100	2.0gph barb outlet x .160 barb outlet	100
SPCV20-250	2.0gph barb outlet x .160 barb outlet	250
SPCV20-1000	2.0gph barb outlet x .160 barb outlet	1000

Self piercing barb: easy to install, no tools required.

1.5 psi internal check valve: helps prevent low dripper drainage, holds back 3-1/2' column of water. Can be used on all drip line brands.

Anti-siphon operation: prevent contaminants from being drawn into the dripper.

Pressure compensating: delivers the same flow from 7psi to 50psi.

Self-cleaning action: exclusive flow path design regulates flow and provides continuous self-cleaning action during operation.