

WATERPROOF WIRE CONNECTORS

SA-101 WIRE CONNECTOR



Our connectors have less than .1% voltage leakage to ground, the lowest in the industry. This means by keeping moisture out and electricity in you will reduce your service call-backs and increase system efficiency.

- Wire range: 9 #20 to 2 #14 w/2 #18.
- Zero failure rate with over 25,000,000 in use worldwide.
- Pre-filled with XR compound, or empty.
- Fast, reliable splicing - reducing labor costs.
- Your choice of wire nuts or crimp. (sleeves)
- UV resistant.

STOCK NO

SA101

STANDARD SHIPPING UNIT

2,400

SA-102 WIRE CONNECTOR



Has all the benefits of the SA101, but designed to accommodate up to three 10-gauge UF wires. Ideal for low voltage lighting cable. Note that our connectors conveniently work with crimp sleeves or wire nuts.

- Wire range: up to 3 #10.
- Zero failure rate after 18 years in use.
- Works great for low voltage lighting.
- Pre-filled with XR compound, or empty.
- Your choice of wire nuts or crimp. (sleeves)
- UV resistant.

SA102

2,400

SPI-F SPLICE-ALL WIRE CONNECTOR



Ideal for low voltage lighting wire splices. Our largest wire connector—accommodates up to four 8-gauge lighting wires and allows 2 splice capability.

- Large capacity
- Multi-splice capability
- Pre-filled with XR compound, or empty.
- Large gray wire nut included
- UV resistant.

SPI-F

600